



All-in-One IP Touch Screen Service Tester

LCDA-1

Before

Supported IP Cameras	
Brand	IP Camera Models
ACTi	ACD-2100, SCD-2200, ACM-4200, AEK-1001B, SED-2120, SED-2120B, ACD-2200
A-MTK	AM9730M, AM9539, AM323M, AM3519, AM6121
Arecont Vision	AV1000 series, AV5000 series, AV 8000 series
autoIP	GV-NC-201B, GV-NC-201VO, GV-NC-102D, GV-NC-102DO
AXIS	205, 206, 207, 210, 211, 221, 231D, 232D, Q1755, P1311 ONVIF Profile S: M3014 w/ Firmware v5.21
Bosch	ONVIF Profile S: NBC-455-P w/ Firmware v1.07.26.00
D-link	DCS-6815, DCS-6817, DCS-6818, DCS-6615 ONVIF Profile S: DCS-2210 w/ Firmware v1.00.00
DVTel	CF-3111, CM-3111, CM-4021
DynaColor Diva Protocol	NH060, NH070, NH101, NH210, NH061, NH221, NH062, NH102, V1, V6
DynaColor IP PTZ	DH510e, DH610e, DH701e, DH811+e
GE	TVC-MP1B-S, TVC-MP2B-S, TVD-MP1D-S, TVD-MP2D-S/E
IQinVision	IQ752, IQ511
Level One	FCS-3071, FCS-1131, FCS-1141
Optelecom-NKF	Sequa BC series, Sequa FD series
ONVIF	ONVIF conformance device (compatible with ONVIF Conformance Test v1.01.1.26)
Panasonic	DG-NP304 ONVIF Profile S: WV-SC385 w/ Firmware v1.44

Firmware Upgrade w/ Support for ONVIF Profile S

Supported IP Cameras	
Brand	IP Camera Models
AXIS	M3014 w/ Firmware v5.21
Bosch	NBC-455-P w/ Firmware v1.07.26.00
D-link	DCS-2210 w/ Firmware v1.00.00
Panasonic	WV-SC385 w/ Firmware v1.44



IP Camera Configuration				
Model	Streaming Format	Advanced Streaming Option	Default Streaming Port	Streaming Protocol
ACTi	MPEG-4 MJPEG	ON/OFF	7070	RTP+RTSP
Arecont Vision	MJPEG	ON/OFF	80	HTTP
autoIP	MPEG-4 MJPEG	ON/OFF	554	RTP+RTSP
AXIS	MPEG-4 MJPEG	ON/OFF	554 80	RTP+RTSP HTTP
D-link	MPEG-4 MJPEG	ON/OFF	554	RTP+RTSP
DVTel	MPEG-4 MJPEG	ON/OFF	554	RTP+RTSP
DynaColor Diva Protocol	MPEG-4 MJPEG	ON/OFF	554	RTP+RTSP
DynaColor IP PTZ	MPEG-4 MJPEG	ON/OFF	80	HTTP
GE	MPEG-4 MJPEG	ON/OFF	554	RTP+RTSP
IQinVision	MJPEG	ON/OFF	80	HTTP
Level One	MPEG-4 MJPEG	ON/OFF	554	RTP+RTSP
Optelecom-NKF	MPEG-4 MJPEG	ON/OFF	554	RTP+RTSP
ONVIF	MJPEG	ON/OFF	554	RTP+RTSP
Panasonic	MJPEG	ON/OFF	80	HTTP
Planet	MJPEG	ON/OFF	554	RTP+RTSP
Sony	MPEG-4 MJPEG	ON/OFF	80	HTTP
ViVoTek	MPEG-4 MJPEG	ON/OFF	554 80	RTP+RTSP HTTP